

Technical Data Sheet

L 62 Eurotop

Product Description

L 62 is a fast drying, high quality two-component acid-curing wood floor finish for various wood species of hardwood floors. As is typical of acid-curing finishes, **L 62** provides a vibrant, rich color with finely detailed grain definition to hardwood floors, including all exotic species of wood. **L 62** is used as its own system with 3 different sheens available: gloss, semi-gloss, and matt. As an option, it can be used **with UniQuick Primer (Special "X" Sealer)**, a special sealer for a very fast drying, first coat primer (see technical data sheet).

Specifications

Components:	Glycol ether Proprietary	Coverage:	450-500 sq.ft./gallon
Clarity:	Slightly yellow	Sheen:	gloss, semi-gloss, matt
Scent :	Alcohol	Stability:	Excellent
Body:	Thick	Leveling:	Excellent
Texture:	Smooth	Defoaming:	N/A
Density:	1.008	Dry Time:	1 hour
Solid Content:	46%	Cure Time:	8-10 days
Packaging:	5 Liter (1.3 Gal.), 10 Ltr. (2.6 Gal.)	Shelf Life:	1 year unopened
Chem. Resistance:	Excellent	Flash Point:	100 ° F

Application Instructions

Shake well before use. After final sanding, the surface to be treated must be completely clean and dry. **L 62** must be mixed with **Hardener** at a ratio of 10:1 and used within 8 hours. The mixed product is then applied in 2-3 coats by brush, roller or applicator. After the coat has dried, intermediate screening may be performed using a 120-150 grit screen. Vacuum thoroughly. If tacking is required, use water. Maintain adequate ventilation. Allow to dry completely before applying next coat. Insufficient ventilation, lower temperatures, increased coat thickness or erratic air humidity may delay drying considerably.

Maintenance and Care

Regular cleaning and care with compatible products is essential for extended floor life and beauty. For best results, use **L94 Cleaner** for basic cleaning and tough stain removal. Before allowing regular traffic, use VOC-free **Everclear** for regular maintenance and a self shining, non-slip floor. We recommend the installation of floor mats at each entry to keep out undue dirt, mud and grit.

System Recommendations

For optimum results, and a brilliant effect on the floor, we recommend the complete **Berger-Seidle System. AquaChoice TrowelFiller, UniQuick Primer (Special "X" Sealer for a 'higher' effect), ToughSeal** and a maintenance coat of **Everclear**. Do not use **L 62** over waterborne finishes. **L 62** has a 1 year shelf life from production date.

Safety Precautions

L 62 is flammable. **L 62** is harmful if inhaled, swallowed or absorbed through the skin. Causes skin and eye irritation. May cause severe allergic reaction and respiratory sensitization. Keep away from flame and ignition sources. Keep container closed. Avoid breathing vapor. Use chemical cartridge respirator for organic compounds. Avoid contact with eyes, skin or clothing. Use with adequate ventilation. Wash thoroughly after handling. Keep out of reach of children. Disposal should comply with local, state and federal regulations.

Manufacturer's Recommendation

This Technical Data Sheet is based on extensive research and wide-ranging experience and is meant to assist you. Restrictive information and precautions have not been avoided in order to reduce risk or fault. Technical Data Sheets do not contain all applications or events that could occur with different species of wood, installation, techniques and finishing. Therefore, you cannot be released from the obligation to contact the manufacturer in cases of doubt, to make your own tests on site and to be critically attentive during the job process. The contents of this data sheet are not legally binding and does not establish any contractual legal relationship. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. This information is subject to change without further notice.